

Tractor trailed mist blowers with double fan

OPTIMAL FOR SPRAYING CITRUS AND FRUIT TREES WITH HIGHER VEGETATION DENSITY. THE UPPER FAN ENABLE A DEEP PENETRATION OF THE CROWN OF THE TREES.

TECHNICAL SPECIFICATIONS:

PUMP

IMOVILLI or COMET diaphragm pump, 60 bar, 170L/min.

ELECTRIC REGULATOR

Four sections electric DPM regulator

TANKS:

Main tank in polyethylene. Capacity: 2000L.

Auxiliary tanks: rinse tank and hand-washing tank.

VENTILATION:

- 800 mm lower fan with 10 aluminium blades.
Gearbox (2 gears and deadlock).
Stainless steel turbine.
Stainless steel arch with 14 anti-drip adjustable nozzle holders. Ceramic discs.
Air flow deflector: a fix helix corrects the air flow that arrives to the fan direction.
- 700 mm upper turbine with 8 nylon blades.
Hydraulic engine.
Stainless steel arch with 14 anti-drip adjustable nozzle holders. Ceramic discs.
Hydraulic lifting of the upper turbine.
Deflector: hydraulic aileron to target the liquid to the crown of the tree.

FRAME:

- Electro-welded frame made of steel sheet pleated in cold.

WHEELS:

- Two 10.0/75-15,3" wheels.

- One jockey wheel.

INCLUDED ACCESORIES:

Traffic light kit, lateral foldable step, "anti-leaf" protector, articulated towbar, one homocinetic PTO shaft kit and one anti-pollution hydro-injector.

