

ROGUE AGRICULTURE

SPECS

Sizes Available	1 furrow, 2 furrow, 3 furrow & 4 furrow
Hitch	Adjustable CATIII
Discs	26" x 6 mm discs with 5 hole PCD
Hubs	Heavy duty triple seal double angular contact bearing hub with adjustable pitch for accurate settings
Shanks	25mm fixed RoqTuf shanks with sheer bolt system
Trash Wheel	heavy duty fully adjustable trash wheel with 6mm coulters for tracking
Toolbar construction	Boxed 16mm beam type frame w
Recommended Power requirements	<ul style="list-style-type: none"> 1 Furrow +40kw 2 Furrow +50kw 3 Furrow +60kw 4 Furrow +70kw

Disc Ploughs



ROGUE AGRICULTURE

SPECS

Sizes Available	1 furrow, 2 furrow, 3 furrow & 4 furrow
Hitch	Pre set CATII
Mould Boards	16" standard mould board
Frogs	Standard Frog configuration to accommodate land slide, sheer, shin and 16" mould board
Shanks	30mm RoqTuf shanks with sheer bolt system
Shank spacing	Fully adjustable
Toolbar construction	Boxed HS channel beam type frame
Power requirements	1 Furrow +30kw 2 Furrow +40kw 3 Furrow +50kw 4 Furrow +65kw

Mould board Ploughs

