

CP CLASSIC

ROBUST AND ERGONOMIC

For more than 4 decades the CP Classic range has been the preferred choice by agricultural, horticultural and amenity users world-wide, as the most durable, robust and accurate agro-chemical applicator.

Its unique diaphragm pump system and integrated pressure control system ensure many years of tranquility and adequate and accurate protection of your crops. Its ergonomic conception gives greater comfort when performing intensive tasks.

Technical specifications:

- ✓ Lid with Separate seal and air vent for secure locking
- ✓ Low mesh strainer to filter out dirt with supplementary filter in trigger
- ✓ Wide filler hole to prevent overflow when filling
- ✓ Reinforced hose for greater pressure resistance
- ✓ High resistance GRP (Glassfibre Reinforced Plastic) lance
- ✓ Multi-nozzle adapter for different spraying applications
- ✓ UV stabilized polypropylene tank for a durable yet lightweight sprayer
- ✓ All working parts mounted inside the tank to prevent damage
- ✓ Unique diaphragm pump very resistant to water impurities
- ✓ Pressure control valve with fixed spraying settings (Low & High)
- ✓ Few moving parts of which none are exposed to friction, thus ensuring resistance to dirt in the spray liquid and a low maintenance level
- ✓ Brass components for excellent durability
- ✓ Adjustable re-inforced lever for left / right hand operation
- ✓ Ergonomic reinforcement / Parts protected from damage by tank skirt



Mini Mac Ring**

Tri-Nozzle attachment for young orchard trees
***Sold Separately



Nozzles included: Yellow hollow cone and green anvil

Color	Volume (L/ha)
Yellow	140
Green	50




Spray Shield
Available Separately



Measuring jug included
*depending on model



Straps with support and carrying handle



Mini Mac Ring

- ✓ Tri-nozzle attachment on Knapsack Sprayers
- ✓ Attachment made specifically to fit on CP Range
- ✓ Aluminium Frame
- ✓ ALBUZ ATR Yellow Hollow cone nozzles x 3



	CP 15 CLASSIC	CP3 CLASSIC
Reference	846255	846320
Tank litres	15 L	20 L
Material	Polypropylene	
Filler neck	140 mm	
Max working pressure	3 bar (45 psi)	
Total weight	4,75 kg	5 kg
Harness material	Polyethylene pads with polyester fibre braiding	
Lance length	500 mm	
Hose length	1360 mm	

